

Model : K-98B

Electrical specification		Uplink	Downlink
Frequency Range	GSM	890 ~ 915MHZ	935 ~ 960MHZ
	DCS	1710 ~ 1785MHZ	1805 ~ 1880MHZ
Max .Gain		55db	60db
Max .Output Power		12dbm	15dbm
Band width	GSM	25M	25M
	DCS	75M	75M
Automatic Level Control	≥ 15 dB, auto shut off after 15dB		
Noise Figure	≤ 6 dB		
V.S.W.R	≤ 2.5		
Group Delay	$\leq 0.5\mu$ s		
Frequency stability	≤ 0.01 ppm		
I /O Port	N-Female		
Impedance	50 Ohm		
Reliability	To the GB6993-86 standard		
Electromagnetic compatibility	To the ETS300 694-4 standard		
Operating Temperature	From -25°C to +85°C		
Dimensions	240 x182 x 22 mm		
Weight	≤ 1.5 KG		
Power Supply	AC110V-240V 50Hz to 12V DC/2A		
Function	A) Power supply LED B) Export power LED		
coverage area	1000 m2		

www.kiantelecom.com

ceiling antenna + 10m cable + 10m cable + log-periodic directional antenna

repeater

GSM/DCS(900/1800MHz) P/N: K-98B